



Power Amplifiers at a Glance

	330A	400M	760A	860A	870A	880M	888	MC-8
Number of Channels	2 - Stereo	1 - Mono	2 - Dual-Mono	2 - Dual-Mono	2 - Dual-Mono	1 - Mono	1 - Mono	2 thru 7
Power Output - 8Ω	125 W/ch.	400 W	130 W/ch.	200 W/ch.	300 W/ch.	800 W	888 W	250 W/ch.
Power Output - 4Ω	250 W/ch.	650 W	260 W/ch.	400 W/ch.	600 W/ch.	1600 W	1776 W	500 W/ch.
Power Output - 2Ω	325 W/ch.	750 W	500 W/ch.	800 W/ch.	1200 W/ch.	2400 W	3550 W *	n/a
Power Output - Mono	400 W	n/a	500 W	800 W	1200 W	n/a	n/a	n/a
Configuration	Balanced	Balanced	Balanced	Balanced	Balanced	Balanced	Balanced	Fully Balanced
Balanced inputs	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Single-ended inputs	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
S/N Ratio @ full power	> 100dB	> 106dB	> 104dB	> 106dB	> 106dB	> 106dB	> 120dB	> 105dB
THD @ 1kHz, full power	< 0.05 %	< 0.05 %	< 0.04 %	< 0.04 %	< 0.04 %	< 0.04 %	< 0.04 %	< 0.05 %
IMD	< 0.02 %	< 0.02 %	< 0.01 %	< 0.01 %	< 0.006 %	< 0.006 %	< 0.006 %	< 0.005 %
Output Binding Posts	1 pair / ch.	1 pair	1 pair / ch.	1 pair / ch.	2 pairs / ch.	2 pairs	2 pairs	1 pair / ch.
RS-232 Port	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
12V Trigger Input/Output	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Weight (lbs.)	33	33	45	90	98	98	230	194 (7-ch)
Dimensions (w" x h" x d")	16.9 x 3.5 x 14	16.9 x 3.5 x 14	18.8 x 4.0 x 17.5	18.8 x 7.4 x 17.5	18.8 x 7.4 x 17.5	18.8 x 7.4 x 17.5	22 x 14 x 27	17.4 x 13.4 x 21

* With 230V AC mains version