

# MOON CD5.3 Disc Player Specifications

<b>Configuration</b>	Single-ended
<b>Front Panel Controls</b>	Stand by • Random play mode • Programming mode • Display (time modes & on/off) • Open/Close CD Drawer • Stop • Play & Pause • Previous Track • Next Track
<b>Front Panel Display</b>	Track number • Time (elapsed or remaining for track or disc)
<b>Front Panel LED Indicators</b>	Programming • Scan • Random • Repeat (disc and track)
<b>DAC / Digital Filter</b>	BurrBrown PCM1730E
<b>Frequency Response (full range) / (audible)</b>	2Hz - 72kHz +0/-3dB / 20Hz - 20kHz +0/-0.2dB
<b>THD @ 1kHz, 0dBFS (A-weighted)</b>	< 0.001 %
<b>IMD</b>	< 0.003 %
<b>Dynamic Range</b>	> 114dB
<b>Signal-to-noise ratio</b>	> 114dB @ full output
<b>Slew Rate</b>	50V/μs
<b>Channel Separation</b>	> 112dB
<b>Low Level Linearity</b>	±1.0dB to below 110dBFS
<b>Intrinsic Jitter</b>	< 50 picoseconds RMS
<b>Single-ended Analog Outputs</b>	1 pair RCA
<b>Balanced Analog Outputs</b>	1 pair XLR - <b>OPTIONAL</b>
<b>Digital Output</b>	S/PDIF (RCA)
<b>Max. Analog Output @ 0dBFS - RCA</b>	2.0 Volts @ 50 Ω
<b>Max. Analog Output @ 0dBFS - XLR</b>	4.0 Volts @ 25 Ω - <b>OPTIONAL</b>
<b>Digital Output Impedance S/PDIF</b>	75 Ω @ 0.5 Volts
<b>Available Faceplate Finishes</b>	Black and Silver
<b>Remote Control</b>	All-Aluminum Full Function
<b>Power Consumption @ idle</b>	15 Watts
<b>AC Power Requirements</b>	120V / 60Hz 240V / 50Hz
<b>Fuse Replacement - 120V / 230V</b>	0.5A short slow blow / 0.25A short slow blow
<b>Shipping weight</b>	26 lbs / 12 kgs
<b>Dimensions (W x H x D)</b>	17.0 x 4.9 x 14.5 in. (43.2 x 12.5 x 36.8 cm.)

Features & specifications are subject to change without notice.