

## MOON i.5 Integrated Amplifier Specifications

<b>Configuration</b>	Single-ended / 2-channel
<b>Class of operation - Amplifier</b>	A/AB
<b>Single Ended Inputs (RCA)</b>	5 pairs
<b>Input Sensitivity</b>	370mV - 3.0V RMS
<b>Input Impedance</b>	11,000 $\Omega$
<b>Tape Output</b>	1 pair
<b>Preamplifier Output</b>	1 pair
<b>Output Power @ 8 <math>\Omega</math></b>	40 Watts per channel
<b>Output Power @ 4 <math>\Omega</math></b>	80 Watts per channel
<b>Output Impedance</b>	0.04 $\Omega$
<b>Damping Factor</b>	> 200
<b>Signal-to-noise Ratio</b>	101dB @ full power
<b>Maximum Output Voltage</b>	20 Volts
<b>Slew Rate</b>	20V/ $\mu$ s
<b>Maximum Current</b>	14 amperes
<b>Frequency Response</b>	10Hz - 100kHz (+0/-3dB)
<b>Crosstalk @ 1kHz</b>	-78dB
<b>IMD</b>	< 0.07%
<b>THD (20Hz - 20kHz @ 1 watt / @ 40 watts)</b>	< 0.015% / < 0.03%
<b>Available Faceplate Finishes</b>	
	Black and Silver
<b>Remote Control</b>	Full Function
<b>Power Consumption @ idle</b>	10 Watts
<b>AC Power Requirements</b>	120V / 60Hz 240V / 50Hz
<b>Fuse Replacement - 120V</b>	4A long fast blow
<b>Fuse Replacement - 230V</b>	2A long fast blow
<b>Shipping weight</b>	20 lbs / 8 kgs
<b>Dimensions (W x H x D)</b>	16.88 x 3.5 x 14.75 in. (42.9 x 8.9 x 37.5 cm.)

Features & specifications are subject to change without notice.