

MOON Integrated Amplifiers at a Glance

	MOON i.5	MOON i-1	MOON i3.3	MOON i5.3	MOON 600i	MOON i-7	MOON 700i
Configuration	2-channel	2-channel	2-channel	Dual-Mono	Dual-Mono	Dual-Mono	Dual-Mono
Power Output - 8Ω	40 W/ch.	50 W/ch.	100 W/ch.	85 W/ch.	125 W/ch.	150 W/ch.	175 W/ch.
Power Output - 4Ω	80 W/ch.	100 W/ch.	200 W/ch.	130 W/ch.	250 W/ch.	250 W/ch.	350 W/ch.
Single-ended inputs (RCA)	5	5	4	5	4	5	5
Balanced inputs (XLR)	n/a	n/a	optional (1)	n/a	1	1	1
Front panel input	1/8" mini-jack	1/8" mini-jack	1/8" mini-jack	no	no	no	no
Headphone output	yes	yes	yes	no	no	no	no
Variable level output	yes	yes	yes	yes	yes	yes	yes
Fixed level output	no	no	yes	yes	yes	yes	yes
Tape Monitor Loop	no	no	no	no	no	1	1
DAC / Digital input	no	no	optional	no	no	no	no
Phono Stage	no	no	optional	no	no	no	no
S/N Ratio @ Full Power	101dB	101dB	110dB	97dB	120dB	114dB	120dB
THD @ Full Power	< 0.03%	< 0.02%	< 0.05%	< 0.15%	< 0.04%	< 0.05%	< 0.04%
12V Trigger Output	no	no	yes	no	yes	yes	yes
RS-232 Port	no	yes	yes	no	yes	yes	yes
Infra-Red (IR) Input	no	yes	yes	yes	yes	yes	yes
SimLink	no	yes	yes	no	yes	yes	yes
Home-Theater Gain Bypass	no	no	no	yes	yes	yes	yes
Remote Control	CRM	CRM	CRM	FRM-2	FRM-2	FRM-2	FRM-2
Weight (lbs.)	20	22	28	29	48	58	60
Dimensions (W" x H" x D")	16.88 x 3.5 x 14.75	16.88 x 3.5 x 14.75	16.88 x 3.5 x 14.75	17.0 x 3.9 x 16.2	18.8 x 4.0 x 18.1	18.8 x 5.4 x 18.1	18.8 x 5.4 x 18.1